

# Fabric Data Sheet

Product : **PC6511250**                      Style : PW                      Customer Spec:

Description : 200gsm/PW/Innega S 940 Den/1250mm

<b>Warp Fibre</b>	AF	<b>Fibre</b>	Ends/10cm  95.7 ±2.5
	AF243	940 Den Innega S 30tpm	

<b>Weft Fibre</b>	AF	<b>Fibre</b>	Picks/10cm  95.7 ±2.5
	AF243	940 Den Innega S 30tpm	

<b>Leno Yarn</b>	113dTex x 2 White Polyester
------------------	-----------------------------

### Tolerances/Testing/Frequency

#### Product Quality Plan                      C

Check	Test Method	Nominal	Tolerance.
Mass	001/2/8	200	±5            gsm
Width	003	1250	-0, +10mm
Ends/10cm	004/005	95.7	±2.5
Picks/10cm	004/005	95.7	
Picks/Inch	010	24.31	
Check	Test Method	Maximum	
Weft Bow	006	30 mm/mt width	
Warp Bow	007	5 mm/mt length	
Nominal Length (metres)		103	
Construction	012	Verify	
Thickness	011	Verify	

Test Methods details refer to information as set in Sigmatex Quality Manual

<b>Special Instruction :</b>	
------------------------------	--

This document is un-controlled and is not subject to any up-dates which Sigmatex may undertake in the future