

SAFETY DATA SHEET



Date Issued : 04/06/2009
MSDS No : WC-753 PART A
Date-Revised : 05/16/2012
Revision No : 1

WC-753 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WC-753 PART A
GENERAL USE: Polyurethane resin
CHEMICAL FAMILY: Isocyanate terminated polyglycol mixture

MANUFACTURER

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin, CA 92780

Customer Service Number: (714) 734-8450

Fax: (714) 734-8929

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300
or (703) 527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE AND ODOR: Colorless liquid with a slight odor.

IMMEDIATE CONCERNS: May cause eye and skin irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

POTENTIAL HEALTH EFFECTS

EYES: Irritating. May cause tearing, reddening, and swelling. May cause slight corneal injury.

SKIN: Causes irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

INGESTION: May cause irritation with symptoms including abdominal pain, nausea, vomiting, and diarrhea.

INHALATION: May be harmful if inhaled. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to the respiratory system.

MEDICAL CONDITIONS AGGRAVATED: May cause or aggravate dermatitis and asthma.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

WC-753 PART A

Chemical Name	Wt.%	CAS
poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane]	40 - 50	9042-82-4
4,4'-Diphenylmethane diisocyanate	15 - 25	101-68-8
Methylenediphenyl Diisocyanate	15 - 25	26447-40-5
Dicyclohexylmethane-4,4'-diisocyanate	10 - 20	5124-30-1
Solvent naphtha, petroleum, light aromatic	< 1	64742-95-6
Xylene	< 1	1330-20-7
1,2,4-trimethylbenzene	< 0.3	95-63-6
Ethylbenzene	< 0.2	100-41-4
Toluene	0.005	108-88-3
Phenyl mercuric acetate (60% as Hg)	0.002	62-38-4

4. FIRST AID MEASURES

EYES: Immediately rinse with water. Remove contact lenses. Hold eyelids apart and flush eyes with water for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. DO NOT induce vomiting. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 96.1°C (205°F) Pensky-Martens CC

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or alcohol foam.

EXPLOSION HAZARDS: Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

RELEASE NOTES: US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

WC-753 PART A

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane]	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
4,4'-Diphenylmethane diisocyanate	TWA	0.02	0.2	0.005	0.05	0.005 ^[1]	0.05 ^[1]
	STEL	NE	NE	NE	NE	NE	NE
Methylenediphenyl Diisocyanate	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Dicyclohexylmethane-4,4'-diisocyanate	TWA	NE	NE	0.005	0.054	0.01 ^[2]	0.11 ^[2]
	STEL	NE	NE	NE	NE	NE	NE
Solvent naphtha, petroleum, light aromatic	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Xylene	TWA	100	435	100	434	NE	NE
	STEL	NE	NE	150	651	NE	NE
1,2,4-trimethylbenzene	TWA	NE	NE	25	123	25 ^[1]	125 ^[1]
	STEL	NE	NE	NE	NE	NE	NE
Ethylbenzene	TWA	100	435	100	434	100 ^[1]	435 ^[1]
	STEL	NE	NE	125	543	125 ^[1]	545 ^[1]
Toluene	TWA	200	NE	50	188	100 ^[1]	375 ^[1]
	STEL	300	NE	NE	NE	150 ^[1]	560 ^[1]
Phenyl mercuric acetate (60% as Hg)	TWA	NE	NE	NE	NE	NE ^[1]	0.01 ^[1]
	STEL	NE	NE	NE	NE	NE ^[3]	0.03 ^[3]
OSHA TABLE COMMENTS:							
1. NIOSH REL							
2. NIOSH REL (ceiling)							
3. NIOSH REL (skin)							

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels

WC-753 PART A

below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid

ODOR: Slight

COLOR: Colorless

pH: Not Applicable

PERCENT VOLATILE: 1.5

VAPOR PRESSURE: < 0.1 mmHg at 25°C (77°F)

VAPOR DENSITY: Heavier than air

BOILING POINT: Decomposes

FLASHPOINT AND METHOD: 96.1°C (205°F) Pinsky-Martens CC

SOLUBILITY IN WATER: Insoluble, reacts slowly with water

SPECIFIC GRAVITY: 1.120 (water=1) at 25°C (77°F)

VISCOSITY: 4150 Centipoise at 25°C (77°F)

VOC (Volatile Organic Compound): 16.700 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

POLYMERIZATION: Product may foam when exposed to heat and moisture.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

INCOMPATIBLE MATERIALS: Water, strong bases, alcohols, amines, metals, and oxidizing agents.

11. TOXICOLOGICAL INFORMATION**TOXICITY TO ANIMALS**

WC-753 PART A

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane]	Not Established	Not Established	Not Established
4,4'-Diphenylmethane diisocyanate	> 10000 mg/kg	> 5000 mg/kg	2.24 mg/l (1 h)
Methylenediphenyl Diisocyanate	Not Established	Not Established	Not Established
Dicyclohexylmethane-4,4'-diisocyanate	9900 mg/kg	> 10000 mg/kg	0.29 to 0.30 mg/l (4 h of aerosols)
Solvent naphtha, petroleum, light aromatic	Not Established	Not Established	Not Established
Xylene	4300 mg/kg	14100 uL/kg	4550 ppm (4 h)
1,2,4-trimethylbenzene	12.7 g/kg	Not Established	18 g/m ³
Ethylbenzene	3500 mg/kg	17800 uL/kg	Not Established
Toluene	636 mg/kg	2 to 14 g/kg	26700 ppm (1h)
Phenyl mercuric acetate (60% as Hg)	41 mg/kg	Not Established	Not Established

CARCINOGENICITY

Chemical Name	IARC Status
4,4'-Diphenylmethane diisocyanate	3
Ethylbenzene	2B
Toluene	3

IARC: This product contains substances that are classified as possible carcinogens to humans.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION) LAND**

NOTE: Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute health hazard. Chronic health hazard

WC-753 PART A

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS	Comments
4,4'-Diphenylmethane diisocyanate	15 - 25	101-68-8	Diisocyanate Compounds (Category Code N120)
Dicyclohexylmethane-4,4'-diisocyanate	10 - 20	5124-30-1	Diisocyanate Compounds (Category Code N120)
Phenyl mercuric acetate (60% as Hg)	0.002	62-38-4	Mercury Compounds (Category Code N458)

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt.%	CERCLA RQ
4,4'-Diphenylmethane diisocyanate	15 - 25	5,000 lbs.
Xylene	< 1	100 lbs.
Ethylbenzene	< 0.2	1,000
Toluene	0.005	1,000 lbs.
Phenyl mercuric acetate (60% as Hg)	0.002	100 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Chemical Name	Wt.%	Listed
Ethylbenzene	< 0.2	Cancer
Toluene	0.005	<ul style="list-style-type: none"> ● Cancer ● Developmental Toxicity
Phenyl mercuric acetate (60% as Hg)	0.002	<ul style="list-style-type: none"> ● Developmental Toxicity

OSHA HAZARD COMM. RULE: The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA**WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Toxic

Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

Class D-2B: Material causing other toxic effects (Toxic).

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS CLASS: The D1A classification applies for this material in aerosol or mist form.

EUROPEAN COMMUNITY

WC-753 PART A**EEC LABEL SYMBOL AND CLASSIFICATION**

"T" - Toxic



"Xn" - Harmful

RISK PHRASES

R20: Harmful by inhalation.

R23: Toxic by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitization by inhalation and skin contact.

R45: May cause cancer.

R46: May cause heritable genetic damage.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

R65: Harmful: may cause lung damage if swallowed.

SAFETY PHRASES

S1/2: Keep locked up and out of reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of water and soap.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S46: If swallowed, seek medical advice immediately and show this container or label.

S53: Avoid exposure - obtain special instructions before use.


S62: If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label.

16. OTHER INFORMATION**REASON FOR ISSUE:** Revision**APPROVED BY:** Michael Rose **TITLE:** R & D Manager**PREPARED BY:** Gus Alidad

REVISION SUMMARY: This MSDS replaces the 04/06/2009 MSDS. Revised: **Section 1:** REASON FOR ISSUE. **Section 3:** Wt.%. **Section 5:** HAZARDOUS DECOMPOSITION PRODUCTS. **Section 9:** PHYSICAL STATE, VAPOR DENSITY. **Section 13:** EMPTY CONTAINER. **Section 15:** CERCLA REGULATORY, STATE REGULATIONS, WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM), CALIFORNIA PROPOSITION 65, WHMIS CLASS.

HMIS RATING

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		1
PERSONAL PROTECTION		X

NFPA CODES**HMIS RATINGS NOTES:** Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.